

FSMR25-9-8-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR2598SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.1204
CouplingMaterial	303 Stainless Steel
noOfScrews	4
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	9
boreB2Mm	8
lenghtLInch	1.5
lenghtLMm	38.1
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	18.3
Bore2ShaftPenetrationMm	18.3
StaticTorqueNm	5.66

NonReversingTorqueNm	2.83
ReversingTorqueNm	1.42
TorsionalStiffnessDeg/Nm	0.41
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529046357
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FSMR25-9-8-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr25-9-8-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>