

FSMR32-14-14-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR321414A



Extra afbeelding



Specificaties

| | |
|--------------------------------|---------------|
| Buitendiameter (inch) | 1.25 |
| Gewicht (kg) | 0.0731 |
| CouplingMaterial | Aluminum |
| noOfScrews | 4 |
| D2OuterDiameterOD | 31.8 |
| nmax(rpm) | 6000 |
| UNSPSCcode | 31163003 |
| boreB1Mm | 14 |
| boreB2Mm | 14 |
| lengthLInch | 1.75 |
| lengthLMm | 44.5 |
| MaterialSpecification | 7075-T651 Bar |
| Bore1ShaftPenetrationMm | 21.4 |
| Bore2ShaftPenetrationMm | 21.4 |
| StaticTorqueNm | 5.08 |

| | |
|---------------------------------|---|
| NonReversingTorqueNm | 2.54 |
| ReversingTorqueNm | 1.27 |
| TorsionalStiffnessDeg/Nm | 0.71 |
| AngularMisalignmentDeg | 3 |
| ParallelMisalignmentMm | 0.38 |
| AxialMotionMm | 0.25 |
| couplingBoreTolerance | +0.025 mm / -0.000 mm |
| couplingShaftTolerance | +0.000 mm / -0.013 mm |
| ScrewType | Alloy Steel |
| ScrewFinish | Black Oxide |
| SeatingTorqueNm | 7.2 |
| certifications | ISO-9001-2008 REACH ROHS2 Conflict Minerals |
| UPC | 634529011003 |
| TariffCode | 8483.60.8000 |
| Merk | Ruland Manufacturing |

Beschrijving

FSMR32-14-14-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr32-14-14-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>