

# FSMR38-19-13-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR381913A



## Extra afbeelding



## Specificaties

<b>Buitendiameter (inch)</b>	1.5
<b>Gewicht (kg)</b>	0.1265
<b>CouplingMaterial</b>	Aluminum
<b>noOfScrews</b>	4
<b>D2OuterDiameterOD</b>	38.1
<b>nmax(rpm)</b>	6000
<b>UNSPSCcode</b>	31163003
<b>boreB1Mm</b>	19
<b>boreB2Mm</b>	13
<b>lengthLInch</b>	2.25
<b>lengthLMm</b>	57.2
<b>MaterialSpecification</b>	7075-T651 Bar
<b>Bore1ShaftPenetrationMm</b>	27.3
<b>Bore2ShaftPenetrationMm</b>	27.3
<b>StaticTorqueNm</b>	9.04

<b>NonReversingTorqueNm</b>	4.52
<b>ReversingTorqueNm</b>	2.26
<b>TorsionalStiffnessDeg/Nm</b>	0.63
<b>AngularMisalignmentDeg</b>	3
<b>ParallelMisalignmentMm</b>	0.76
<b>AxialMotionMm</b>	0.38
<b>couplingBoreTolerance</b>	+0.025 mm / -0.000 mm
<b>couplingShaftTolerance</b>	+0.000 mm / -0.013 mm
<b>ScrewType</b>	Alloy Steel
<b>ScrewFinish</b>	Black Oxide
<b>SeatingTorqueNm</b>	7.2
<b>certifications</b>	ISO-9001-2008 REACH ROHS2 Conflict Minerals
<b>UPC</b>	634529210956
<b>TariffCode</b>	8483.60.8000
<b>Merk</b>	Ruland Manufacturing

## Beschrijving

FSMR38-19-13-A Ruland Manufacturing Beam couplings

## Product URL

<https://aandrijftechniek.nl/product/fsmr38-19-13-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>