


FSMR38-20-13-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR382013A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.5
Gewicht (kg)	0.1231
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	38.1
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	20
boreB2Mm	13
lenghtLInch	2.25
lenghtLMm	57.2
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	27.3
Bore2ShaftPenetrationMm	27.3
StaticTorqueNm	11.75

NonReversingTorqueNm	5.88
ReversingTorqueNm	2.94
TorsionalStiffnessDeg/Nm	0.77
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.76
AxialMotionMm	0.38
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	7.2
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529211014
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FSMR38-20-13-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr38-20-13-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>