

HTD 1904 8M 30 GATES POWERGRIP?? HTD?? Endless timing belts GATES

SKU: 7G0081904-30



Specificaties

Gewicht (kg/m)	0.36
Spoed (mm)	8
Hoogte riem (mm)	5.6
Breedte riem (mm)	30
Spoorlengte (mm)	1904
Materiaal riem	Chloroprene
Koordmateriaal	Glass
Riemprofiel	8M
numberOfTeethZ	238
toothWidthMM	3.4
Gewicht (kg)	0.36
Omschrijving (EN)	The PowerGrip?? HTD?? synchronous belt curvilinear tooth form ensures an optimised load distribution leading to high power transmission in low speed and high torque applications. PowerGrip?? HTD?? 3M and 5M belts are suitable for domestic appliances, office machines, electric hand tools and for applications in the processing and chemical industry. PowerGrip?? HTD?? 8M, 14M and 20M belts are used in high performance drives in the machine tool, paper and textile industries where durability and low maintenance are required. These synchronous belts have a larger, more robust curvilinear tooth profile for increased capacity, as compared to other timing belts. Precisely formed and accurately spaced elastomeric teeth ensure correct positioning in the pulley grooves. Special curvilinear tooth form improves stress distribution and allows higher overall loading. Neoprene body provides protection against grime, grease, oil and moisture.

Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+100
EAN-code	5412571279757
Aangepaste code	4010.3600.00
Status	Normal
oringColour	Black
Land van herkomst	GB
beltBackSide	Smooth
Tandvorm	HTD Design
sided	Single Sided
StatConductive	No
fabricMaterial	Nylon
beltEnd	Endless
sprockCompatable	PowerGrip HTD
Merk	GATES
Gewicht (kg/m)	0.36
Spoed (mm)	8
Breedte riem (mm)	30
Materiaal riem	Chloroprene
Riemprofiel	8M
Gewicht (kg)	0.36
Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+100
Land van herkomst	GB

Beschrijving

HTD 1904 8M 30 GATES POWERGRIP?? HTD?? Endless timing belts

Product URL

<https://aandrijftechniek.nl/product/htd-1904-8m-30-gates-powergrip-htd-endless-timing-belts-gates/>