

## 5M1150JB/3 GATES Polyflex??? JB??? Banded V-belts GATES

SKU: 4G0005M1150/3



### Specificaties

<b>Gewicht (kg/m)</b>	0.105
<b>Spoed (mm)</b>	8
<b>Hoogte riem (mm)</b>	5.6
<b>Breedte riem (mm)</b>	20
<b>Spoorlengte (mm)</b>	920
<b>Materiaal riem</b>	Chloroprene
<b>Koordmateriaal</b>	Glass
<b>Riemprofiel</b>	8M
<b>numberOfTeethZ</b>	115
<b>toothWidthMM</b>	3.4
<b>Gewicht (kg)</b>	0.105
<b>Omschrijving (EN)</b>	<p>The PowerGrip?? HTD?? synchronous belt curvilinear tooth form ensures an optimised load distribution leading to high power transmission in low speed and high torque applications. PowerGrip?? HTD?? 3M and 5M belts are suitable for domestic appliances, office machines, electric hand tools and for applications in the processing and chemical industry. PowerGrip?? HTD?? 8M, 14M and 20M belts are used in high performance drives in the machine tool, paper and textile industries where durability and low maintenance are required. These synchronous belts have a larger, more robust curvilinear tooth profile for increased capacity, as compared to other timing belts. Precisely formed and accurately spaced elastomeric teeth ensure correct positioning in the pulley grooves. Special curvilinear tooth form improves stress distribution and allows higher overall loading. Neoprene body provides protection against grime, grease, oil and moisture.</p>

<b>Minimale temperatuur (??C)</b>	-30
<b>Maximale temperatuur (??C)</b>	+100
<b>EAN-code</b>	5412571290141
<b>Aangepaste code</b>	4010.3500.00
<b>Status</b>	Normal
<b>oringColour</b>	Black
<b>Land van herkomst</b>	GB
<b>beltBackSide</b>	Smooth
<b>Tandvorm</b>	HTD Design
<b>sided</b>	Single Sided
<b>StatConductive</b>	No
<b>fabricMaterial</b>	Nylon
<b>beltEnd</b>	Endless
<b>sprockCompatible</b>	PowerGrip HTD
<b>Merk</b>	GATES

## Beschrijving

HTD 920 8M 20 GATES POWERGRIP?? HTD?? Endless timing belts

## Product URL

<https://aandrijftechniek.nl/product/htd-920-8m-20-gates-powergrip-htd-endless-timing-belts-gates/>