

# LL PU HTD 8M 50 (100M) STEEL GATES SYNCHRO-POWER??

## Roll Stock Open end timing belts PU GATES

SKU: 7G50850ST



### Specificaties

<b>Gewicht (kg/m)</b>	0.25
<b>Spoed (mm)</b>	8
<b>Hoogte riem (mm)</b>	5.6
<b>Breedte riem (mm)</b>	50
<b>Materiaal riem</b>	PU
<b>Koordmateriaal</b>	Steel
<b>Riemprofiel</b>	8M
<b>toothWidthMM</b>	3.4
<b>Gewicht (kg)</b>	0.25
<b>Omschrijving (EN)</b>	Belts are designed for a wide variety of loads, from micro-positioning to high-load and dynamic linear movements. Therefore this type of belt is especially fit for applications in conveyors, linear actuators, synchronous transport, assembly lines, and many more. Endless welded belts can be equipped with a wide variety of backings. Endless welded and open-end rolls in various sizes, constructions and tooth designs. Variety of tooth pitch, cord types, PU resins and coatings available.
<b>Minimale temperatuur (??C)</b>	-5
<b>Maximale temperatuur (??C)</b>	+70

<b>EAN-code</b>	5414465268069
<b>Aangepaste code</b>	3926.9097.90
<b>Status</b>	Normal
<b>oringColour</b>	White
<b>Land van herkomst</b>	DE
<b>Tandvorm</b>	HTD Design
<b>sided</b>	Single Sided
<b>StatConductive</b>	No
<b>beltEnd</b>	Open End
<b>Merk</b>	GATES
<b>Gewicht (kg/m)</b>	0.25
<b>Spoed (mm)</b>	8
<b>Breedte riem (mm)</b>	50
<b>Materiaal riem</b>	PU
<b>Riemprofiel</b>	8M
<b>Gewicht (kg)</b>	0.25
<b>Minimale temperatuur (??C)</b>	-5
<b>Maximale temperatuur (??C)</b>	+70
<b>Land van herkomst</b>	DE

## Beschrijving

LL PU HTD 8M 50 (100M) STEEL GATES SYNCHRO-POWER?? Roll Stock Open end timing belts PU

## Product URL

<https://aandrijftechniek.nl/product/ll-pu-htd-8m-50-100m-steel-gates-synchro-power-roll-stock-open-end-timing-belts-pu-gates/>