

MBC15-4-3-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBC1543A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	15
Buitendiameter (inch)	0.59
Gewicht (kg)	0.009
nmax(rpm)	10000
boreB1Mm	4
boreB2Mm	3
AngularMisalignmentDeg	1.5
ParallelMisalignmentMm	0.1
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
UPC	634529063545
TariffCode	8483.60.8000
ForgedClampScrew	M2

NumberofScrewsEa	2
BoreTolerance	+0.03 mm / -0.00 mm
FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.000 mm / -0.013 mm
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.317 x10 ⁻⁶ kg-m ²
Length(L)	1.076 in (27.3 mm)
StaticTorqueInput	2.5 Nm
NonReversingTorqueInput	1.25 Nm
ReversingTorqueInput	0.63 Nm
TorsionalStiffnessInput	8 Nm/Deg
AxialMotionInput	0.20 mm
Bore1ShaftPenetrationInput	13.1 mm
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

MBC15-4-3-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/mbc15-4-3-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>