

MBC19-4-4-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBC1944A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	19.1
Buitendiameter (inch)	0.75
Gewicht (kg)	0.019
nmax(rpm)	10000
boreB1Mm	4
boreB2Mm	4
AngularMisalignmentDeg	1.5
ParallelMisalignmentMm	0.1
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.21
UPC	634529063637
TariffCode	8483.60.8000
ForgedClampScrew	M2.5

NumberofScrewsEa	2
BoreTolerance	+0.03 mm / -0.00 mm
FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.000 mm / -0.013 mm
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.904 x10 ⁻⁶ kg-m ²
Length(L)	1.306 in (33.2 mm)
StaticTorqueInput	4.5 Nm
NonReversingTorqueInput	2.25 Nm
ReversingTorqueInput	1.13 Nm
TorsionalStiffnessInput	14 Nm/Deg
AxialMotionInput	0.25 mm
Bore1ShaftPenetrationInput	14.5 mm
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

MBC19-4-4-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/mbc19-4-4-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>