

MBC25-12-8-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBC25128A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	25.4
Buitendiameter (inch)	1
Gewicht (kg)	0.031
nmax(rpm)	10000
boreB1Mm	12
boreB2Mm	8
AngularMisalignmentDeg	1.5
ParallelMisalignmentMm	0.1
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529063798
TariffCode	8483.60.8000
ForgedClampScrew	M3

NumberofScrewsEa	2
BoreTolerance	+0.03 mm / -0.00 mm
FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.000 mm / -0.013 mm
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	2.693 x10 ⁻⁶ kg-m ²
Length(L)	1.345 in (34.2 mm)
StaticTorqueInput	6.8 Nm
NonReversingTorqueInput	3.40 Nm
ReversingTorqueInput	1.70 Nm
TorsionalStiffnessInput	27 Nm/Deg
AxialMotionInput	0.30 mm
Bore1ShaftPenetrationInput	15.9 mm
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

MBC25-12-8-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/mbc25-12-8-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>