

MBC33-11-8-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBC33118A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Buitendiameter (inch)	1.313
Gewicht (kg)	0.07
nmax(rpm)	10000
boreB1Mm	11
boreB2Mm	8
AngularMisalignmentDeg	1.5
ParallelMisalignmentMm	0.15
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529141045
TariffCode	8483.60.8000
ForgedClampScrew	M3

NumberofScrewsEa	2
BoreTolerance	+0.03 mm / -0.00 mm
FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.000 mm / -0.013 mm
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	10.915 x10 ⁻⁶ kg-m ²
Length(L)	1.700 in (43.2 mm)
StaticTorqueInput	13.6 Nm
NonReversingTorqueInput	6.80 Nm
ReversingTorqueInput	3.40 Nm
TorsionalStiffnessInput	45 Nm/Deg
AxialMotionInput	0.40 mm
Bore1ShaftPenetrationInput	20.4 mm
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

MBC33-11-8-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/mbc33-11-8-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>