

MBCK33-15-15-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBCK331515A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Buitendiameter (inch)	1.313
Gewicht (kg)	0.062
nmax(rpm)	10000
boreB1Mm	15
boreB2Mm	15
AngularMisalignmentDeg	1.5
ParallelMisalignmentMm	0.15
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529165447
TariffCode	8483.60.8000
ForgedClampScrew	M3

NumberofScrewsEa	2
BoreTolerance	+0.03 mm / -0.00 mm
FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.000 mm / -0.013 mm
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	1.097 x 10 ⁻⁵ kg-m ²
Length(L)	1.700 in (43.2 mm)
Keyway(K1)	5 mm
Keyway(K2)	5 mm
StaticTorqueInput	13.6 Nm
NonReversingTorqueInput	6.80 Nm
ReversingTorqueInput	3.40 Nm
TorsionalStiffnessInput	45 Nm/Deg
AxialMotionInput	0.40 mm
Bore1ShaftPenetrationInput	20.4 mm
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

MBCK33-15-15-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/mbck33-15-15-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>