

# MBCK41-19-17-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610MBCK411917A



## Extra afbeelding



## Specificaties

<b>Materiaal</b>	Aluminium
<b>Buitendiameter (mm)</b>	41.3
<b>Buitendiameter (inch)</b>	1.625
<b>Gewicht (kg)</b>	0.118
<b>nmax(rpm)</b>	10000
<b>boreB1Mm</b>	19
<b>boreB2Mm</b>	17
<b>AngularMisalignmentDeg</b>	2
<b>ParallelMisalignmentMm</b>	0.25
<b>ScrewType</b>	Alloy Steel
<b>ScrewFinish</b>	Black Oxide
<b>SeatingTorqueNm</b>	4.6
<b>UPC</b>	634529166628
<b>TariffCode</b>	8483.60.8000
<b>ForgedClampScrew</b>	M4

<b>NumberofScrewsEa</b>	2
<b>BoreTolerance</b>	+0.03 mm / -0.00 mm
<b>FinishSpecification</b>	Anodize
<b>Style</b>	Clamp
<b>ShaftTolerance</b>	+0.000 mm / -0.013 mm
<b>FasteningDimensions</b>	Metric
<b>ISO 9001 (2008)</b>	Yes
<b>REACH</b>	Yes
<b>ROHS2</b>	Yes
<b>ConflictMinerals</b>	Yes
<b>MomentofInertia</b>	3.013 x 10 <sup>-5</sup> kg-m <sup>2</sup>
<b>Length(L)</b>	2.035 in (51.7 mm)
<b>Keyway(K1)</b>	6 mm
<b>Keyway(K2)</b>	5 mm
<b>StaticTorqueInput</b>	28.0 Nm
<b>NonReversingTorqueInput</b>	14.00 Nm
<b>ReversingTorqueInput</b>	7.00 Nm
<b>TorsionalStiffnessInput</b>	63 Nm/Deg
<b>AxialMotionInput</b>	0.50 mm
<b>Bore1ShaftPenetrationInput</b>	24.0 mm
<b>BellowsAttachmentMethod</b>	Epoxy
<b>UNSPC</b>	31163018
<b>Merk</b>	Ruland Manufacturing

## Beschrijving

MBCK41-19-17-A Ruland Manufacturing Bellow couplings

## Product URL

<https://aandrijftechniek.nl/product/mbck41-19-17-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>