


# MSPB-36-SS Ruland Manufacturing Shaft collar Ruland Manufacturing

SKU: 610MSPB36SS



## Extra afbeelding



## Specificaties

|                              |                                 |
|------------------------------|---------------------------------|
| <b>Buitendiameter (mm)</b>   | 57                              |
| <b>Gewicht (kg)</b>          | 0.1687                          |
| <b>boreType</b>              | Round                           |
| <b>OriginalType</b>          | Shaft Collar - Balanced         |
| <b>SteelMaterial</b>         | 303 Stainless Steel             |
| <b>widthWMM</b>              | 15                              |
| <b>UNSPSCcode</b>            | 31162811                        |
| <b>boreB1Mm</b>              | 36                              |
| <b>ClearanceDiameterMm</b>   | 62.4                            |
| <b>MaterialSpecification</b> | 303 Stainless Steel             |
| <b>ScrewType</b>             | 18-8 300 Series Stainless Steel |
| <b>ScrewFinish</b>           | Bright                          |
| <b>UPC</b>                   | 634529214305                    |
| <b>TariffCode</b>            | 8483.60.8000                    |
| <b>ForgedClampScrew</b>      | M6 x 18                         |

|                            |                       |
|----------------------------|-----------------------|
| <b>NumberofScrewsEa</b>    | 2                     |
| <b>ScrewLocation??</b>     | 23.24 mm              |
| <b>WidthTolerance</b>      | +0.076 mm / -0.254 mm |
| <b>BoreTolerance</b>       | +0.050 mm / +0.012 mm |
| <b>SeatingTorque</b>       | 9.6 Nm                |
| <b>FinishSpecification</b> | Bright No Plating     |
| <b>BoreStyle</b>           | Round                 |
| <b>Style</b>               | Clamp                 |
| <b>ShaftTolerance</b>      | +0.000 mm / -0.013 mm |
| <b>FasteningDimensions</b> | Metric                |
| <b>ISO 9001 (2008)</b>     | Yes                   |
| <b>REACH</b>               | Yes                   |
| <b>ROHS2</b>               | Yes                   |
| <b>ConflictMinerals</b>    | Yes                   |
| <b>RecommendedGap</b>      | 1.59 mm               |
| <b>Merk</b>                | Ruland Manufacturing  |

## Beschrijving

MSPB-36-SS Ruland Manufacturing Shaft collar

## Product URL

<https://aandrijftechniek.nl/product/mspb-36-ss-ruland-manufacturing-shaft-collar-ruland-manufacturing/>