


MWC15-3-3-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWC1533A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.59
Gewicht (kg)	0.0083
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	15
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	3
boreB2Mm	3
lengthLInch	0.866
lengthLMm	22
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	10.6
Bore2ShaftPenetrationMm	10.6
StaticTorqueNm	0.85

NonReversingTorqueNm	0.43
ReversingTorqueNm	0.21
TorsionalStiffnessDeg/Nm	4.44
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.12
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529054802
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWC15-3-3-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mwc15-3-3-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>