

MWC15-4-4-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWC1544SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.59
Gewicht (kg)	0.0222
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	15
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	4
boreB2Mm	4
lenghtLInch	0.866
lenghtLMm	22
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	10.6
Bore2ShaftPenetrationMm	10.6
StaticTorqueNm	1.3

NonReversingTorqueNm	0.65
ReversingTorqueNm	0.33
TorsionalStiffnessDeg/Nm	2.23
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.12
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529054956
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWC15-4-4-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mwc15-4-4-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>