

MWC20-5-4-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWC2054SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.787
Gewicht (kg)	0.0533
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	20
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	5
boreB2Mm	4
lengthLInch	1.102
lengthLMm	28
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	13.6
Bore2ShaftPenetrationMm	13.6
StaticTorqueNm	2

NonReversingTorqueNm	1
ReversingTorqueNm	0.5
TorsionalStiffnessDeg/Nm	0.98
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.12
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529055144
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWC20-5-4-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mwc20-5-4-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>