

MWC20-6-6-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWC2066A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.787
Gewicht (kg)	0.0193
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	20
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	6
lenghtLInch	1.102
lenghtLMm	28
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	13.6
Bore2ShaftPenetrationMm	13.6
StaticTorqueNm	1.15

NonReversingTorqueNm	0.58
ReversingTorqueNm	0.29
TorsionalStiffnessDeg/Nm	2.48
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.12
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529055229
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWC20-6-6-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mwc20-6-6-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>