


MWC25-8-8-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWC2588SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.984
Gewicht (kg)	0.0847
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	25
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	8
boreB2Mm	8
lenghtLInch	1.181
lenghtLMm	30
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	14.2
Bore2ShaftPenetrationMm	14.2
StaticTorqueNm	5.1

NonReversingTorqueNm	2.55
ReversingTorqueNm	1.28
TorsionalStiffnessDeg/Nm	0.58
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529055519
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWC25-8-8-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mwc25-8-8-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>