

MWS20-5-5-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWS2055A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.787
Gewicht (kg)	0.0144
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	20
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	5
boreB2Mm	5
lenghtLInch	0.787
lenghtLMm	20
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	9.6
Bore2ShaftPenetrationMm	9.6
StaticTorqueNm	1.3

NonReversingTorqueNm	0.65
ReversingTorqueNm	0.33
TorsionalStiffnessDeg/Nm	2.01
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.12
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.92
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529056226
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWS20-5-5-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mws20-5-5-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>