

MWS25-8-6-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWS2586A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.984
Gewicht (kg)	0.0266
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	25
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	8
boreB2Mm	6
lengthLInch	0.945
lengthLMm	24
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	11.7
Bore2ShaftPenetrationMm	11.7
StaticTorqueNm	3.42

NonReversingTorqueNm	1.71
ReversingTorqueNm	0.86
TorsionalStiffnessDeg/Nm	1.22
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.76
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529056585
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWS25-8-6-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mws25-8-6-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>