

MWS30-12-8-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610MWS30128SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.181
Gewicht (kg)	0.1252
CouplingMaterial	303 Stainless Steel
noOfScrews	4
D2OuterDiameterOD	30
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	12
boreB2Mm	8
lengthLInch	1.181
lengthLMm	30
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	14.2
Bore2ShaftPenetrationMm	14.2
StaticTorqueNm	10

NonReversingTorqueNm	5
ReversingTorqueNm	2.5
TorsionalStiffnessDeg/Nm	0.46
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529056745
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

MWS30-12-8-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/mws30-12-8-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>