

PC2 14MGT 2590 68 GATES Poly Chain® GT™2 Endless timing belts PU GATES

SKU: 7G3142590-68GT2



Specificaties

Spoed (mm)	14
Hoogte riem (mm)	10.2
Breedte riem (mm)	68
Spoorlengte (mm)	2590
Materiaal riem	PU
Koordmateriaal	Aramid
Riemprofiel	14MGT
numberOfTeethZ	185
toothWidthMM	6
Gewicht (kg)	1.337
Omschrijving (EN)	Poly Chain® GT™2 has been designed for optimum performance on high torque, low speed drives in any industrial application. This lightweight belt features increased power ratings of up to 40% higher than previous constructions while maintaining the same long service life. Poly Chain® GT™2 operates on Poly Chain® GT™ pulleys. These belts make an excellent alternative to roller chains, requiring neither re-tensioning nor lubrication. Space-saving, weight-saving and money-saving, Poly Chain® GT™2 drives over a long and reliable service life. x000D_ Teeth and body are made of a lightweight polyurethane compound, specially blended for adhesion to the cords and fabric. Uniquely formulated polyurethane makes the belt tough and virtually immune to abrasion and chemicals. The aramid tensile cords provide extraordinary power-carrying capacity.
Minimale temperatuur (°C)	-54

Maximale temperatuur (°C)	+85
EAN-code	5414465328084
Aangepaste code	3926.9097.90
Status	Normal
oringColour	Black
Land van herkomst	US
beltBackSide	Ribbed
Tandvorm	GT Design
sided	Single Sided
StatConductive	No
fabricMaterial	Nylon
beltEnd	Endless
sprockCompatable	Poly Chain GT
Merk	GATES

Beschrijving

PC2 14MGT 2590 68 GATES Poly Chain® GT™2 Endless timing belts PU

Product URL

<https://aandrijftechniek.nl/product/pc2-14mgt-2590-68-gates-poly-chain-gt2-endless-timing-belts-pu-gates/>