

# PC2 14MGT 2800 68 GATES Poly Chain® GT™2 Endless timing belts PU GATES

SKU: 7G3142800-68GT2



## Specificaties

<b>Spoed (mm)</b>	14
<b>Hoogte riem (mm)</b>	10.2
<b>Breedte riem (mm)</b>	68
<b>Spoorlengte (mm)</b>	2800
<b>Materiaal riem</b>	PU
<b>Koordmateriaal</b>	Aramid
<b>Riemprofiel</b>	14MGT
<b>numberOfTeethZ</b>	200
<b>toothWidthMM</b>	6
<b>Gewicht (kg)</b>	1.45
<b>Omschrijving (EN)</b>	<p>Poly Chain® GT™2 has been designed for optimum performance on high torque, low speed drives in any industrial application. This lightweight belt features increased power ratings of up to 40% higher than previous constructions while maintaining the same long service life. Poly Chain® GT™2 operates on Poly Chain® GT™ pulleys. These belts make an excellent alternative to roller chains, requiring neither re-tensioning nor lubrication. Space-saving, weight-saving and money-saving, Poly Chain® GT™2 drives over a long and reliable service life. x000D_ Teeth and body are made of a lightweight polyurethane compound, specially blended for adhesion to the cords and fabric. Uniquely formulated polyurethane makes the belt tough and virtually immune to abrasion and chemicals. The aramid tensile cords provide extraordinary power-carrying capacity.</p>
<b>Minimale temperatuur (°C)</b>	-54

<b>Maximale temperatuur (°C)</b>	+85
<b>EAN-code</b>	5412571232769
<b>Aangepaste code</b>	3926.9097.90
<b>Status</b>	Normal
<b>oringColour</b>	Black
<b>Land van herkomst</b>	US
<b>beltBackSide</b>	Ribbed
<b>Tandvorm</b>	GT Design
<b>sided</b>	Single Sided
<b>StatConductive</b>	No
<b>fabricMaterial</b>	Nylon
<b>beltEnd</b>	Endless
<b>sprockCompatible</b>	Poly Chain GT
<b>Merk</b>	GATES

## Beschrijving

PC2 14MGT 2800 68 GATES Poly Chain® GT™2 Endless timing belts PU

## Product URL

<https://aandrijftechniek.nl/product/pc2-14mgt-2800-68-gates-poly-chain-gt2-endless-timing-belts-pu-gates/>