

PCMR10-3-3-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR1033SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.375
Gewicht (kg)	0.0054
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	9.5
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	3
boreB2Mm	3
lenghtLInch	0.563
lenghtLMm	14.3
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	6.7
Bore2ShaftPenetrationMm	6.7
StaticTorqueNm	0.85

NonReversingTorqueNm	0.43
ReversingTorqueNm	0.21
TorsionalStiffnessDeg/Nm	6.65
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M1.6
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.29
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529048665
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR10-3-3-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr10-3-3-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>