

PCMR13-3-3-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR1333SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.5
Gewicht (kg)	0.0142
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	12.7
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	3
boreB2Mm	3
lengthLInch	0.75
lengthLMm	19.1
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	9
Bore2ShaftPenetrationMm	9
StaticTorqueNm	1.24

NonReversingTorqueNm	0.62
ReversingTorqueNm	0.31
TorsionalStiffnessDeg/Nm	3.26
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529048672
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR13-3-3-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr13-3-3-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>