

# PCMR16-5-3-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR1653A



## Extra afbeelding



## Specificaties

<b>Buitendiameter (inch)</b>	0.625
<b>Gewicht (kg)</b>	0.0083
<b>CouplingMaterial</b>	Aluminum
<b>noOfScrews</b>	2
<b>D2OuterDiameterOD</b>	15.9
<b>nmax(rpm)</b>	6000
<b>UNSPSCcode</b>	31163003
<b>boreB1Mm</b>	5
<b>boreB2Mm</b>	3
<b>lengthLInch</b>	0.8
<b>lengthLMm</b>	20.3
<b>MaterialSpecification</b>	7075-T651 Bar
<b>Bore1ShaftPenetrationMm</b>	9.6
<b>Bore2ShaftPenetrationMm</b>	9.6
<b>StaticTorqueNm</b>	1.36

<b>NonReversingTorqueNm</b>	0.68
<b>ReversingTorqueNm</b>	0.34
<b>TorsionalStiffnessDeg/Nm</b>	4.78
<b>AngularMisalignmentDeg</b>	3
<b>ParallelMisalignmentMm</b>	0.2
<b>AxialMotionMm</b>	0.13
<b>couplingBoreTolerance</b>	+0.025 mm / -0.000 mm
<b>couplingShaftTolerance</b>	+0.000 mm / -0.013 mm
<b>ScrewCapSize</b>	M2
<b>ScrewType</b>	Alloy Steel
<b>ScrewFinish</b>	Black Oxide
<b>SeatingTorqueNm</b>	0.6
<b>certifications</b>	ISO-9001-2008 REACH ROHS2 Conflict Minerals
<b>UPC</b>	634529031469
<b>TariffCode</b>	8483.60.8000
<b>Merk</b>	Ruland Manufacturing

## Beschrijving

PCMR16-5-3-A Ruland Manufacturing Beam couplings

## Product URL

<https://aandrijftechniek.nl/product/pcmr16-5-3-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>