

PCMR16-5-4-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR1654SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.625
Gewicht (kg)	0.0227
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	15.9
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	5
boreB2Mm	4
lengthLInch	0.8
lengthLMm	20.3
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	9.6
Bore2ShaftPenetrationMm	9.6
StaticTorqueNm	1.81

NonReversingTorqueNm	0.91
ReversingTorqueNm	0.45
TorsionalStiffnessDeg/Nm	2.53
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529048726
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR16-5-4-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr16-5-4-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>