

PCMR22-5-5-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR2255A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.875
Gewicht (kg)	0.024
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	22.2
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	5
boreB2Mm	5
lenghtLInch	1.063
lenghtLMm	27
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	12.7
Bore2ShaftPenetrationMm	12.7
StaticTorqueNm	2.26

NonReversingTorqueNm	1.13
ReversingTorqueNm	0.57
TorsionalStiffnessDeg/Nm	1.49
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529031599
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR22-5-5-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr22-5-5-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>