

PCMR22-7-5-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR2275SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.875
Gewicht (kg)	0.0611
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	22.2
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	7
boreB2Mm	5
lengthLInch	1.063
lengthLMm	27
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	12.7
Bore2ShaftPenetrationMm	12.7
StaticTorqueNm	2.49

NonReversingTorqueNm	1.25
ReversingTorqueNm	0.62
TorsionalStiffnessDeg/Nm	1.19
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529048863
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR22-7-5-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr22-7-5-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>