

PCMR25-10-6-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR25106A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.0357
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	10
boreB2Mm	6
lengthLInch	1.25
lengthLMm	31.8
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	14.7
Bore2ShaftPenetrationMm	14.7
StaticTorqueNm	3.39

NonReversingTorqueNm	1.7
ReversingTorqueNm	0.85
TorsionalStiffnessDeg/Nm	1.8
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529057698
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR25-10-6-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr25-10-6-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>