


PCMR25-8-7-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR2587SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.0953
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	8
boreB2Mm	7
lengthLInch	1.25
lengthLMm	31.8
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	14.7
Bore2ShaftPenetrationMm	14.7
StaticTorqueNm	4.97

NonReversingTorqueNm	2.49
ReversingTorqueNm	1.24
TorsionalStiffnessDeg/Nm	0.83
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529048979
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR25-8-7-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr25-8-7-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>