

# PCMR29-6-6-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR2966SS



## Extra afbeelding



## Specificaties

|                         |                     |
|-------------------------|---------------------|
| Buitendiameter (inch)   | 1.125               |
| Gewicht (kg)            | 0.1508              |
| CouplingMaterial        | 303 Stainless Steel |
| noOfScrews              | 2                   |
| D2OuterDiameterOD       | 28.6                |
| nmax(rpm)               | 6000                |
| UNSPSCcode              | 31163003            |
| boreB1Mm                | 6                   |
| boreB2Mm                | 6                   |
| lengthLInch             | 1.5                 |
| lengthLMm               | 38.1                |
| MaterialSpecification   | 303 Stainless Steel |
| Bore1ShaftPenetrationMm | 17.6                |
| Bore2ShaftPenetrationMm | 17.6                |
| StaticTorqueNm          | 7.12                |

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| <b>NonReversingTorqueNm</b>     | 3.56                                        |
| <b>ReversingTorqueNm</b>        | 1.78                                        |
| <b>TorsionalStiffnessDeg/Nm</b> | 0.47                                        |
| <b>AngularMisalignmentDeg</b>   | 3                                           |
| <b>ParallelMisalignmentMm</b>   | 0.38                                        |
| <b>AxialMotionMm</b>            | 0.25                                        |
| <b>couplingBoreTolerance</b>    | +0.025 mm / -0.000 mm                       |
| <b>couplingShaftTolerance</b>   | +0.000 mm / -0.013 mm                       |
| <b>ScrewCapSize</b>             | M4                                          |
| <b>ScrewType</b>                | Alloy Steel                                 |
| <b>ScrewFinish</b>              | Black Oxide                                 |
| <b>SeatingTorqueNm</b>          | 4.6                                         |
| <b>certifications</b>           | ISO-9001-2008 REACH ROHS2 Conflict Minerals |
| <b>UPC</b>                      | 634529049211                                |
| <b>TariffCode</b>               | 8483.60.8000                                |
| <b>Merk</b>                     | Ruland Manufacturing                        |

## Beschrijving

PCMR29-6-6-SS Ruland Manufacturing Beam couplings

## Product URL

<https://aandrijftechniek.nl/product/pcmr29-6-6-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>