

PCMR29-8-8-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR2988SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.125
Gewicht (kg)	0.1453
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	28.6
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	8
boreB2Mm	8
lenghtLInch	1.5
lenghtLMm	38.1
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	17.6
Bore2ShaftPenetrationMm	17.6
StaticTorqueNm	6.78

NonReversingTorqueNm	3.39
ReversingTorqueNm	1.7
TorsionalStiffnessDeg/Nm	0.5
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529049266
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR29-8-8-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr29-8-8-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>