

PCMR32-12-9-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PCMR32129A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.25
Gewicht (kg)	0.064
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	31.8
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	12
boreB2Mm	9
lenghtLInch	1.5
lenghtLMm	38.1
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	17.6
Bore2ShaftPenetrationMm	17.6
StaticTorqueNm	5.88

NonReversingTorqueNm	2.94
ReversingTorqueNm	1.47
TorsionalStiffnessDeg/Nm	1.1
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529032244
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PCMR32-12-9-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/pcmr32-12-9-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>