

# PCV 14MGT 2660 20 GATES POLYCHAIN?? CARBON VOLT Endless timing belts PU GATES

SKU: 7G3142660-20PCV



## Specificaties

<b>Spoed (mm)</b>	14
<b>Hoogte riem (mm)</b>	10.2
<b>Breedte riem (mm)</b>	20
<b>Spoorlengte (mm)</b>	2660
<b>Materiaal riem</b>	PU
<b>Koordmateriaal</b>	Carbon
<b>Riemprofiel</b>	14MGT
<b>numberOfTeethZ</b>	190
<b>toothWidthMM</b>	6
<b>Gewicht (kg)</b>	0.415

<b>Omschrijving (EN)</b>	The power you want, the safety you never had! Anti-static power transmission belts are a necessity in volatile environments, like those found in the energy, agriculture, and petrochemical industries. The Poly Chain?? Carbon??? Volt?? belt is the only belt in the market that provide an industry-leading solution that meets ISO 9563 standard for static conductivity over the full lifetime of the belt. Its patented static-conductive jacket construction transfers static electricity safely to carbon tensile cords, away from the driven side of the application - making it your safest and strongest option for applications in ATEX environments. Gates uses patented Carbon Fibre tensile cords for increased horsepower rating, compactness and flexibility, while also allowing the use of backside. When combined with Gates?? Poly Chain?? GT?? sprockets, you'll have a lightweight, long-lasting, maintenance-free system that's more than a match for roller chain. Static conductive (ISO 9563) and can as such be used in the conditions described in the directive 2014/34/EU- ATEX. Chemically resistant polyurethane compound that ensures optimum adhesion with the carbon tensile cords. Carbon fibre reinforcement for high strength and length stability.
<b>Minimale temperatuur (??C)</b>	-54
<b>Maximale temperatuur (??C)</b>	+85
<b>EAN-code</b>	5414465492730
<b>Aangepaste code</b>	3926.9097.90
<b>Status</b>	Normal
<b>oringColour</b>	Black
<b>Land van herkomst</b>	US
<b>beltBackSide</b>	Ribbed
<b>Tandvorm</b>	GT Design
<b>sided</b>	Single Sided
<b>StatConductive</b>	Yes
<b>fabricMaterial</b>	Nylon
<b>beltEnd</b>	Endless
<b>sprockCompatable</b>	Poly Chain GT
<b>Merk</b>	GATES
<b>Spoed (mm)</b>	14
<b>Breedte riem (mm)</b>	20
<b>Materiaal riem</b>	PU
<b>Riemprofiel</b>	14MGT
<b>Gewicht (kg)</b>	0.415

<b>Minimale temperatuur (??C)</b>	-54
<b>Maximale temperatuur (??C)</b>	+85
<b>Land van herkomst</b>	US

## Beschrijving

PCV 14MGT 2660 20 GATES POLYCHAIN?? CARBON VOLT Endless timing belts PU

## Product URL

<https://aandrijftechniek.nl/product/pcv-14mgt-2660-20-gates-polychain-carbon-volt-endless-timing-belts-pu-gates/>