

PSMR22-6-6-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PSMR2266SS



Specificaties

Buitendiameter (inch)	0.875
Gewicht (kg)	0.0691
CouplingMaterial	303 Stainless Steel
noOfScrews	4
D2OuterDiameterOD	22.2
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	6
lenghtLInch	1.063
lenghtLMm	27
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	12.7
Bore2ShaftPenetrationMm	12.7
StaticTorqueNm	2.71
NonReversingTorqueNm	1.36
ReversingTorqueNm	0.68
TorsionalStiffnessDeg/Nm	0.95
AngularMisalignmentDeg	3

ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.76
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529050286
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PSMR22-6-6-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/psmr22-6-6-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>