

PSMR25-8-8-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PSMR2588A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.0375
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	8
boreB2Mm	8
lenghtLInch	1.25
lenghtLMm	31.8
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	14.7
Bore2ShaftPenetrationMm	14.7
StaticTorqueNm	3.73

NonReversingTorqueNm	1.87
ReversingTorqueNm	0.93
TorsionalStiffnessDeg/Nm	1.57
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.76
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529033203
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PSMR25-8-8-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/psmr25-8-8-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>