

PSMR29-9-8-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610PSMR2998A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.125
Gewicht (kg)	0.0563
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	28.6
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	9
boreB2Mm	8
lenghtLInch	1.5
lenghtLMm	38.1
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	17.6
Bore2ShaftPenetrationMm	17.6
StaticTorqueNm	6.78

NonReversingTorqueNm	3.39
ReversingTorqueNm	1.7
TorsionalStiffnessDeg/Nm	0.62
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529033517
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

PSMR29-9-8-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/psmr29-9-8-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>