

# Roller chain 16B-2 b.dry, Stainless steel - maintenance-free - JWIS IWIS IWIS

SKU: 100BDD1611CF



## Specificaties

<b>Kettingsontwerp</b>	duplex
<b>Oppervlaktebehandeling</b>	Stainless steel maintenance free
<b>Kettingsmering</b>	Unlubricated
<b>Corrosiebestendig</b>	Ja
<b>Rechte zijplaten</b>	Nee
<b>Minimale breekbelasting volgens ISO (kN)</b>	85
<b>Materiaal</b>	Stainless Steel
<b>Spoed (inch)</b>	1
<b>Spoed (mm)</b>	25.4
<b>Maximale rollerdikte (D1) (mm)</b>	8.28
<b>Breedte tussen binnenplaten (mm)</b>	17.02
<b>Maximale hoogte binnenplaat (H2) (mm)</b>	21
<b>Dwarssteek (Pt) (mm)</b>	31.88
<b>Onderhoudsvrij</b>	Ja
<b>ISO-standaardmaat</b>	16B
<b>ISO-standaard</b>	ISO 606 BS

<b>Eenheden</b>	m
<b>Omschrijving (EN)</b>	<p>b.dry chains are made from corrosion-free, maintenance-free CF stainless steel with an optimized articulated link that represents a masterpiece of high precision. The capabilities of this material are absolutely unparalleled. b.dry products run completely dry, but are still more resistant to wear and corrosion, stronger and have a longer service life than comparable chains.</p> <p>Highlights:</p> <ul style="list-style-type: none"> <li>Properties of individual parts that are perfectly harmonized with each other reduce chain wear and dramatically increase service life.</li> <li>b.dry chains are extremely reliable, withstand high dynamic loads and are corrosion-resistant.</li> <li>b.dry chains are completely dry-running. No lubrication is necessary, thanks to a high-performance plastic friction bearing in the articulated link</li> <li>Extremely high resistance to aggressive media. Information on chemical resistance of the b.dry chains and bush available on request</li> <li>Length tolerances compliant with ISO 606</li> <li>Temperature range: -100 °C to +200 °C</li> <li>No relubrication required</li> <li>Also available as roller chains with attachments or extended pins and as custom-developed chains. ANSI chains also on request.</li> </ul>
<b>accToISO606kN</b>	85
<b>accToANSIkN</b>	85
<b>Merk</b>	IWIS
<b>Materiaal</b>	Stainless Steel
<b>Spoed (inch)</b>	1
<b>Spoed (mm)</b>	25.4

## Beschrijving

Roller chain 16B-2 b.dry, Stainless steel - maintenance-free - JWIS IWIS

## Product URL

<https://aandrijftechniek.nl/product/roller-chain-16b-2-b-dry-stainless-steel-maintenance-free-jwis-iwis-iwis/>