

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCD1033A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	15
Gewicht (kg)	0.0201
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lenghtLInch	0.937
lenghtLMm	23.8
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
UPC	634529081501
TariffCode	8483.60.8000
boreB1Inch	0.1875
outsideDiameterInInput	0.59

ForgedClampScrew	M2
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.0010 lb-in ²
boreB2Inch	0.1875
StaticTorqueInput	15 lb-in
NonReversingTorqueInput	7.5 lb-in
ReversingTorqueInput	3.75 lb-in
TorsionalStiffnessInput	27 lb-in/Deg
ParallelMisalignmentInch	0.002 in
AxialMotionInput	0.004 in
Bore1ShaftPenetrationInput	0.458 in
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	0.458 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-10/>