

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCDE321610A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Gewicht (kg)	0.5693
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lengthLInch	2.519
lengthLMm	64
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529088517
TariffCode	8483.60.8000
boreB1Inch	1.0000
outsideDiameterInInput	2

ForgedClampScrew	M5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.3073 lb-in ²
boreB2Inch	0.6250
StaticTorqueInput	350 lb-in
NonReversingTorqueInput	175 lb-in
ReversingTorqueInput	87.5 lb-in
TorsionalStiffnessInput	595 lb-in/Deg
ParallelMisalignmentInch	0.012 in
AxialMotionInput	0.025 in
Bore1ShaftPenetrationInput	1.192 in
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	1.192 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-101/>