


Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCSK2588A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	25.4
Gewicht (kg)	0.0641
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	8
boreB2Mm	8
lenghtLInch	1.031
lenghtLMm	26.2
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529201046
TariffCode	8483.60.8000

outsideDiameterInInput	1
ForgedClampScrew	M3
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$2.575 \times 10^{-6} \text{ kg-m}^2$
Keyway(K1)	2 mm
Keyway(K2)	2 mm
StaticTorqueInput	5.6 Nm
NonReversingTorqueInput	2.80 Nm
ReversingTorqueInput	1.40 Nm
TorsionalStiffnessInput	10.6 Nm/Deg
ParallelMisalignmentInch	0.00 mm
AxialMotionInput	0.15 mm
Bore1ShaftPenetrationInput	12.7 mm
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	12.7 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1033/>