

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCSK512525A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Gewicht (kg)	0.3889
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	25
boreB2Mm	25
lenghtLInch	1.813
lenghtLMm	46.1
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529204658
TariffCode	8483.60.8000

outsideDiameterInInput	2
ForgedClampScrew	M5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$7.056 \times 10^{-5} \text{ kg-m}^2$
Keyway(K1)	8 mm
Keyway(K2)	8 mm
StaticTorqueInput	39.6 Nm
NonReversingTorqueInput	19.80 Nm
ReversingTorqueInput	9.90 Nm
TorsionalStiffnessInput	98.0 Nm/Deg
ParallelMisalignmentInch	0.00 mm
AxialMotionInput	0.32 mm
Bore1ShaftPenetrationInput	22.2 mm
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	22.2 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1187/>