

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCSK21108A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Gewicht (kg)	0.1265
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lenghtLInch	1.313
lenghtLMm	33.3
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529201169
TariffCode	8483.60.8000
boreB1Inch	0.6250 in
outsideDiameterInInput	1.313

ForgedClampScrew	M3
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.0322 lb-in ²
Keyway(K1)	3/16 in
Keyway(K2)	1/8 in
boreB2Inch	0.5000
StaticTorqueInput	100 lb-in
NonReversingTorqueInput	50 lb-in
ReversingTorqueInput	25 lb-in
TorsionalStiffnessInput	313 lb-in/Deg
ParallelMisalignmentInch	0.00 in
AxialMotionInput	0.008 in
Bore1ShaftPenetrationInput	0.590 in
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	0.635 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1283/>