

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCSK362018A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	57.2
Gewicht (kg)	0.6025
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lengthLInch	2.313
lengthLMm	58.8
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	16
UPC	634529205334
TariffCode	8483.60.8000
boreB1Inch	1.2500 in
outsideDiameterInInput	2.25

ForgedClampScrew	M6
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.4833 lb-in ²
Keyway(K1)	1/4 in
Keyway(K2)	1/4 in
boreB2Inch	1.1250
StaticTorqueInput	450 lb-in
NonReversingTorqueInput	225 lb-in
ReversingTorqueInput	112.5 lb-in
TorsionalStiffnessInput	1000 lb-in/Deg
ParallelMisalignmentInch	0.00 in
AxialMotionInput	0.015 in
Bore1ShaftPenetrationInput	1.050 in
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	1.085 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1300/>