

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCDE2165A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Gewicht (kg)	0.1882
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lengthLInch	1.77
lengthLMm	45
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529088272
TariffCode	8483.60.8000
boreB1Inch	0.3750
outsideDiameterInInput	1.313

ForgedClampScrew	M3
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.0402 lb-in ²
boreB2Inch	0.3125
StaticTorqueInput	100 lb-in
NonReversingTorqueInput	50 lb-in
ReversingTorqueInput	25 lb-in
TorsionalStiffnessInput	253 lb-in/Deg
ParallelMisalignmentInch	0.008 in
AxialMotionInput	0.016 in
Bore1ShaftPenetrationInput	0.842 in
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	0.842 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1333/>