

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCDE36108A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	57.2
Gewicht (kg)	0.8943
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lengthLInch	3.08
lengthLMm	78.2
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	16
UPC	634529091227
TariffCode	8483.60.8000
boreB1Inch	0.6250
outsideDiameterInInput	2.25

ForgedClampScrew	M6
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.6179 lb-in ²
boreB2Inch	0.5000
StaticTorqueInput	450 lb-in
NonReversingTorqueInput	225 lb-in
ReversingTorqueInput	112.5 lb-in
TorsionalStiffnessInput	769 lb-in/Deg
ParallelMisalignmentInch	0.012 in
AxialMotionInput	0.030 in
Bore1ShaftPenetrationInput	1.458 in
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	1.458 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1344/>