

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCS1255A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	19.1
Gewicht (kg)	0.0307
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lengthLInch	0.906
lengthLMm	23
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.21
UPC	634529082164
TariffCode	8483.60.8000
boreB1Inch	0.3125
outsideDiameterInInput	0.75

ForgedClampScrew	M2.5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.0025 lb-in ²
boreB2Inch	0.3125
StaticTorqueInput	25 lb-in
NonReversingTorqueInput	12.5 lb-in
ReversingTorqueInput	6.25 lb-in
TorsionalStiffnessInput	77 lb-in/Deg
ParallelMisalignmentInch	0.00 in
AxialMotionInput	0.004 in
Bore1ShaftPenetrationInput	0.442 in
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	0.442 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1360/>