

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCD512418A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Gewicht (kg)	0.5735
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	24
boreB2Mm	18
lenghtLInch	2.519
lenghtLMm	64
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529148594
TariffCode	8483.60.8000

outsideDiameterInInput	2
ForgedClampScrew	M5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	9.923 x 10 ⁻⁵ kg-m ²
StaticTorqueInput	39.6 Nm
NonReversingTorqueInput	19.80 Nm
ReversingTorqueInput	9.90 Nm
TorsionalStiffnessInput	67.2 Nm/Deg
ParallelMisalignmentInch	0.30 mm
AxialMotionInput	0.64 mm
Bore1ShaftPenetrationInput	30.3 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	30.3 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1412/>